

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name EFOX 60 S30
Chemical name Tert-Butyl 3,5,5-Trimethylperoxyhexanoate - TBPIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial use
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturer AKPA KİMYA AMBALAJ SANAYİ VE TİCARET ANONİM ŞİRKETİ
Yenibosna Merkez Mah. Ladin Sok. No:36/70 Kat:12 34197
Townofis Bahçelievler, İstanbul, TÜRKİYE
Web: www.akpakimya.com
TEL: +90 212 580 55 59
FAX: +90 212 580 55 21
E-mail: info@akpakimya.com
Contact person Export Department - export@akpakimya.com

1.4. Emergency telephone number

Emergency telephone CHEMTREC: TOLL Free 1-800-424-9300 / Local: +1-703-527-3887
For product information AKPA KİMYA: +90 549 558 40 40

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (EC 1272/2008)**

Physical hazards Flam. Liq. 3 - H226; Org. Perox. F - H242
Health hazards Skin Sens. 1 - H317; Asp. Tox. 1 - H304
Environmental hazards Aquatic Acute 1 - H400; Aquatic Chronic 1 - H410

2.2. Label elements**Pictogram****Signal Word****Danger****Hazard statements****H226** Flammable liquid and vapour.

SAFETY DATA SHEET

EFOX 60 S30

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

- H242** Heating may cause a fire.
- H304** May be fatal if swallowed and enters airways.
- H317** May cause an allergic skin reaction.
- H410** Very toxic to aquatic life with long lasting effects.

Precautionary statements

- P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220** Keep away from acids, alkalis, heavy metal compounds, oxidizing material, combustible materials.
- P273** Avoid release to the environment.
- P280** Wear protective gloves/protective clothing/ eye protection/ face protection.
- P301+P310** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352** IF ON SKIN: Wash with plenty of soap and water.
- P333+P313** If skin irritation or rash occurs: Get medical advice/attention.
- P411+P235** Store at temperatures between (-20°C) - (+25°C). Keep cool.
- P501** Dispose of contents/ container in accordance with national regulations.

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Contains

tert-butyl 3,5,5-trimethylperoxyhexanoate, Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

tert-butyl 3,5,5-trimethylperoxyhexanoate		%29-31	
REACH Reg. No: 01-2119498308-25-0005			
CAS Number	13122-18-4	EC Number	236-050-7
Classification			
Org. Perox. D	H242		
Skin Sen. 1	H317		
Aquatic Acute 1	H400		
Aquatic Chronic 1	H410		

SAFETY DATA SHEET

EFOX 60 S30

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated		%69-71	
REACH Reg. No: 01-2119490725-29-0000			
CAS Number	93685-81-5	EC Number	297-629-8
Classification			
Flam. Liq. 3	H226		
Asp. Tok. 1	H304	M(Chronic)=0	
Aquatic Chronic 4	H413		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

Inhalation

Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.

Ingestion

Immediately rinse mouth and drink plenty of water. DO NOT induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!

Skin contact

Remove victim immediately from source of exposure. Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

Protection of first aiders

First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Congestion of the lungs may occur producing severe shortness of breath. May cause stomach pain or vomiting.
Skin contact	Mild dermatitis, allergic skin rash.
Eye contact	May cause blurred vision and serious eye damage.
4.3. Indication of any immediate medical attention and special treatment needed	
Notes for the doctor	Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.

SECTION 5: Firefighting measures

5.1. Extinguishing media	
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder.
Unsuitable extinguishing Media	Halon. Direct water jet.
5.2. Special hazards arising from the substance or mixture	
Specific hazards	In case of fire, toxic gases may be formed. Vapours may form explosive air mixtures even at room temperature. Containers can burst violently when heated, due to excess pressure build-up.
Hazardous decomposition products	Fire causes formation of toxic gases. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks.
5.3. Advice for firefighters	
Protective actions during firefighting	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Face mask, protective gloves and safety helmet.
Special protective equipment for firefighters	Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. If possible, fight fire from protected position. Move container from fire area if it can be done without risk. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control. If risk of water pollution occurs, notify appropriate authorities.

SECTION 6: Accidental release measures

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

6.1. Personal precautions, protective equipment and emergency procedures**Personal precautions**

Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.

6.2. Environmental precautions**Environmental precautions**

Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up**Methods for cleaning up**

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Dike far ahead of larger spills for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections**Reference to the other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Usage precautions**

Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not handle broken packages without protective equipment.

Advice on general occupational hygiene

Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Observe good chemical hygiene practices. Mechanical ventilation or local exhaust ventilation may be required. Container must be kept tightly closed. Protect against direct sunlight.

7.2. Conditions for safe storage, including any incompatibilities**Storage precautions**

Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Store away from: Acids. Alkalis. Heavy metal

SAFETY DATA SHEET

EFOX 60 S30

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

compounds. Oxidising material - Keep away from flammable and combustible materials. Store in closed original container at temperatures between (-20) - (+25)°C. Provide an adequate ventilation system.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control Parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
tert-butyl 3,5,5-trimethylperoxyhexanoate	Workers	Inhalation	Long-term systemic effects	5,6 mg/m ³
	Workers	Skin contact	Long-term systemic effects	3,2 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
tert-butyl 3,5,5-trimethylperoxyhexanoate	Fresh water	0,00051 mg/l
	Marine water	0,000051 mg/l
	Intermittent water	0,0051 mg/l
	Fresh water sediment	0,101 mg/kg
	Marine sediment	0,0101 mg/kg
	Sewage treatment plant	2,6 mg/kg
	Soil	0,0199 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Isolate contaminated clothing and wash before reuse. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Wash promptly with soap & water if skin becomes contaminated.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Wear suitable mask. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14 387 and EN143. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Environmental exposure controls Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties**9.1. Information on basic physical and chemical properties**

Appearance	Clear liquid.
Colour	Colorless.
Odour	Characteristic.
Melting point	Not available.
Flash point	No data available.
Bulk density	Not available.
Density	0,795 ± 0,005 gr/cm ³ @20°C
Solubility(ies)	Partially soluble in water.
Viscosity	No data available.

9.2. Other information

Active Oxygen Content	2,02 - 2,16 %
SADT	55°C

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time. Keep away from heat, sparks, open flames or hot surfaces. – No smoking.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong reducing agents. Bases, alkalis (organic). Organic peroxides/hydroperoxides.

10.6. Hazardous decomposition products

Hazardous decomposition Products During fire, toxic gases (CO, CO₂) are formed.

SECTION 11: Toxicological information

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

11.1. Information on toxicological effects**Toxicological information****tert-butyl 3,5,5-trimethylperoxyhexanoate**

Acute oral toxicity	LD50: 12,905 mg/kg	Species: Rat
Acute dermal toxicity	LD50: >2,500 mg/kg	Species: Rabbit
Acute inhalation toxicity	LC50 (Rat): >0,8 mg/l	Exposure time: 4h

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

Acute oral toxicity	LD50: >5,000 mg/kg	Species: Rat
---------------------	--------------------	--------------

Serious eye damage/irritation: Based on available data the classification criteria are not met.**Skin corrosion/irritation:** Based on available data the classification criteria are not met.**Respiratory or skin sensitisation:****Respiratory sensitisation** Based on available data the classification criteria are not met.**Skin sensitisation** May cause an allergic skin reaction.**Germ cell mutagenicity:**

Based on available data the classification criteria are not met.

Carcinogenicity:

Based on available data the classification criteria are not met.

Reproductive Toxicity - Fertility

Based on available data the classification criteria are not met.

Reproductive Toxicity –

Based on available data the classification criteria are not met.

Development**Specific target organ toxicity - single exposure:**

STOT - Single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure Based on available data the classification criteria are not met.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Inhalation

May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

IngestionMay cause chemical burns in mouth, oesophagus and stomach.
Harmful: may cause lung damage if swallowed.**Skin contact**

May cause skin irritation. May cause sensitisation by skin contact.

Eye contact

May cause temporary eye irritation.

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

12.1. Toxicity Very toxic to aquatic life with long lasting effects.**Ecological information on ingredients.****tert-butyl 3,5,5-trimethylperoxyhexanoate**

Toxicity to fish	LC50, 96h (Oncorhynchus mykiss (rainbow trout)): 7.0 mg/l
Toxicity to algae	EC50, 72h (Pseudokirchneriella subcapitata (green algae)): 0.33 mg/l
Toxicity to microorganisms	EC50, 3h (Bacteria): 327.02 mg/l
Toxicity to daphnia and other aquatic invertebrates	EC50, 48h (Daphnia magna (Water flea)): >0.52 mg/l

Hydrocarbons, C4, 1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

EC50 / 48h	>0.04 mg/l (daphnia magna)
IC50 / 72h	>0.04 mg/l (alga)

12.2. Persistence and degradability**Persistence and degradability** There are no data on the degradability of this product.**12.3. Bio accumulative potential****Bio accumulative potential** No data available on bioaccumulation.**12.4. Mobility in soil****Mobility** The product is partly miscible with water and may spread in the aquatic environment.**12.5. Results of PBT and vPvB assessment****Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.**12.6. Other adverse effects****Other adverse effects** Not known.**SECTION 13: Disposal considerations****13.1. Waste treatment methods****General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered.**Disposal methods**

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Environmental Manager must be informed of all major spillages.

SAFETY DATA SHEET

EFOX 60 S30

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 14: Transport information

General information

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

UN No. (ADR/RID)	3109
UN No. (IMDG)	3109
UN No. (ICAO)	3109
UN No. (ADN)	3109

14.2. UN proper shipping name

Proper Shipping name(ADR/RID)	ORGANIC PEROXIDE TYPE F, LIQUID (tert-butyl 3,5,5-trimethylperoxyhexanoate)
Proper Shipping name (IMDG)	ORGANIC PEROXIDE TYPE F, LIQUID (tert-butyl 3,5,5-trimethylperoxyhexanoate)
Proper Shipping name (ICAO)	ORGANIC PEROXIDE TYPE F, LIQUID (tert-butyl 3,5,5-trimethylperoxyhexanoate)
Proper Shipping name (ADN)	ORGANIC PEROXIDE TYPE F, LIQUID (tert-butyl 3,5,5-trimethylperoxyhexanoate)

14.3. Transport hazard class(es)

ADR/RID class	5.2
ADR/RID label	5.2
IMDG class	5.2
ICAO class/division	5.2
ADN class	5.2

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

**14.6. Special precautions for user**

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS	F-J, S-R
Emergency Action Code	2W
Hazard No. (ADR)	539
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL No data available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information**Key literature references and sources for data**

This SDS is prepared based on the information received from the product owner.

SAFETY DATA SHEET**EFOX 60 S30**

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Classification procedures according to Regulation (EC) 1272/2008	Skin Sens. 1 - H317; Asp. Tox. 1 - H304; Aquatic Acute 1 - H400; Aquatic Chronic 1 - H410: Calculation Method. Flam. Liq. 3 - H226; Org. Perox. F - H242: Expert Judgement	
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.	
Revision comments	Added REACH Number.	
Issued By	Simge ARIK - lab@akpakimya.com	+90 282 361 80 99
Issued Date	21.03.2014	
Revision date	04.04.2018	
Revision	1.0	
Hazard statements in full		
H226	Flammable liquid and vapour.	
H242	Heating may cause a fire.	
H304	May be fatal if swallowed and enters airways.	
H317	May cause an allergic skin reaction.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.